
Shams al Ma'arif of al Buni

Free PDF Ebooks - Free PDF ebooks. KITAB SYAMSUL MA ARIF AL KUBRO FREE PDF. Category:Multilingual texts
Category:Saadia Category:Khotan literature Category:20th-century books// Copyright 2019 Google LLC // Licensed under the
Apache License, Version 2.0 (the "License"); // you may not use this file except in compliance with the License. // You may
obtain a copy of the License at // // // Unless required by applicable law or agreed to in writing, software // distributed under
the License is distributed on an "AS IS" BASIS, // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied. // See the License for the specific language governing permissions and // limitations under the License.

```
#ifndef IREE_UTIL_BLOCK_CALLBACKS_H_ #define IREE_UTIL_BLOCK_CALLBACKS_H_ #include  
"absl/types/optional.h" #include "absl/types/variant.h" namespace iree { namespace internal { // Defines the interface for all  
blocking IO callbacks passed to iree::stream:: // RunBlockingIO. // // |result| is the result of the IO operation. It may be any value  
that the caller // wishes to indicate has happened. It may also be |absl::nullopt| if no IO // operation occurred (e.g., the  
connection was closed by the peer). // // |err| may be any exception that would be passed to the caller. If the caller // wishes to  
ignore |err|, it is fine to pass |absl::nullopt|. // // |blocking_callbacks| should be a vector of optional callbacks that are run //  
before, during and after the IO operation. Each callback should indicate what // state that callback needs to operate in (e.g.,  
blocking, async, error). // // |on_error| is called if any of the callbacks throw an exception. // // |on_close| will be called if the  
|stream| is
```

[Download](#)

